



主要技术参数 Main Specifications

- 线数 (Poles): 02 to 15
- 接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 100\text{M}\Omega$
- 额定电压 (Rated voltage): 50V AC DC
- 额定电流 (Rated current): 1.0A AC DC
- 耐电压 (Withstand Voltage): 500V AC/minute
- 温度范围 (Temperature Range): $-40^\circ\text{C} \sim +110^\circ\text{C}$

NO.	DESCRIPTION	QTY	MATERIAL	PLATING/COLOR
A	Insulator	1	LCP(UL94V-0)	Beige
B	Contacts	2~15	PhosphorBronze	Tin/Nie-plated
C	Solder Tab	2	PhosphorBronze	Tin/Nie-plated

孔位	尺寸	DIM A	DIM B	DIM C	孔位	尺寸	DIM A	DIM B	DIM C
2P		1.25	5.75	3.95	9P		10.00	14.50	12.70
3P		2.50	7.00	5.20	10P		11.25	15.75	13.95
4P		3.75	8.25	6.45	11P		12.50	17.00	15.20
5P		5.00	9.50	7.70	12P		13.75	18.25	16.45
6P		6.25	10.75	8.95	13P		15.00	19.50	17.70
7P		7.50	12.00	10.20	14P		16.25	20.75	18.95
8P		8.75	13.25	11.45	15P		17.50	22.00	20.20

UNITS	mm	QWYCONN® 深圳市启崴源电子有限公司 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.	
MAT'L		PART NO.(INTENDED USE)	TITLE:
FINISH		GH1.25-nPWB	GH1.25卧贴插座
Q'TY	PCS	APPD:	DWG NO.:
		CHKD:	GH1.25-nPWB
		DR: HU 2016.09.28	SCALE
			SHEET
			REV.
			1/1
			1/1
			A