



主要技术参数 Main Specifications

- 线数 (Poles): 02 to 16
- 接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$
- 额定电压 (Rated voltage): 250V AC DC
- 额定电流 (Rated current): 3.0A AC DC
- 耐电压 (Withstand Voltage): 1000V AC/minute
- 温度范围 (Temperature Range): $-25^\circ\text{C} \sim +105^\circ\text{C}$

| | | | | |
|------|------------|-------|----------|-----------------------|
| C | Solder Tab | 2 PCS | Brass | Tin-plated |
| B | Contacts | n PCS | Brass | Tin-plated |
| A | HOUSING | 1 PCS | LCP | UL 94V-0, COLOR:BEIGE |
| ITEM | COMPONENT | Q'TY | MATERIAL | FINISH |

| Circuit | Dimensions (mm) | | | | Circuit | Dimensions (mm) | | | |
|---------|-----------------|-------|-------|-------|---------|-----------------|-------|-------|-------|
| | A | B | C | D | | A | B | C | D |
| 02 | 2.50 | 7.50 | 10.00 | 8.20 | 10 | 22.50 | 27.50 | 30.00 | 28.20 |
| 03 | 5.00 | 10.00 | 12.50 | 10.70 | 11 | 25.00 | 30.00 | 32.50 | 30.70 |
| 04 | 7.50 | 12.50 | 15.00 | 13.20 | 12 | 27.50 | 32.50 | 35.00 | 33.20 |
| 05 | 10.00 | 15.00 | 17.50 | 15.70 | 13 | 30.00 | 35.00 | 37.50 | 35.70 |
| 06 | 12.50 | 17.50 | 20.00 | 18.20 | 14 | 32.50 | 37.50 | 40.00 | 38.20 |
| 07 | 15.00 | 20.00 | 22.50 | 20.70 | 15 | 35.00 | 40.00 | 42.50 | 40.70 |
| 08 | 17.50 | 22.50 | 25.00 | 23.20 | 16 | 37.50 | 42.50 | 45.00 | 43.20 |
| 09 | 20.00 | 25.00 | 27.50 | 25.70 | | | | | |

| | |
|-------------|--------------|
| X ± 0.3 | X° ± 5° |
| .X ± 0.25 | .X° ± 2° |
| .XX ± 0.20 | .XX° ± 1° |
| .XXX ± 0.10 | .XXX° ± 0.5° |

UNITS: mm
 MAT'L: **QWYCONN** 深圳市启崴源电子有限公司
 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.
 PART NO.(INTENDED USE): XH2.54-nAWB
 TITLE: XH2.54卧贴针座
 APPD: DWG NO.: XH2.54-nAWB
 CHKD: SCALE: 1/1 SHEET: 1/1 REV: A
 DR: HU 2016.09.28