



性能:

- 额定电流: 0.5A
- 额定电压: 50V
- 耐电压: 500V
- 接触电阻: ≤ 20mΩ
- 绝缘电阻: 800MΩ
- 工作温度: -25°C~+85°C
- 主体 (材质): PA46, UL94V-0
- 插簧 (材质): 磷青铜, 镀锡

孔位	A	B	C
4	3.00	5.10	7.50
5	4.00	6.10	8.50
6	5.00	7.10	9.50
7	6.00	8.10	10.50
8	7.00	9.10	11.50
9	8.00	10.10	12.50
10	9.00	11.10	13.50
11	10.00	12.10	14.50
12	11.00	13.10	15.50
13	12.00	14.10	16.50
14	13.00	15.10	17.50
15	14.00	16.10	18.50
16	15.00	17.10	19.50
17	16.00	18.10	20.50
18	17.00	19.10	21.50
19	18.00	20.10	22.50
20	19.00	21.10	23.50
21	20.00	22.10	24.50
22	21.00	23.10	25.50
23	22.00	24.10	26.50
24	23.00	25.10	27.50
25	24.00	26.10	28.50
26	25.00	27.10	29.50
27	26.00	28.10	30.50
28	27.00	29.10	31.50
29	28.00	30.10	32.50
30	29.00	31.10	33.50
31	30.00	32.10	34.50
32	31.00	33.10	35.50
33	32.00	34.10	36.50
34	33.00	35.10	37.50
35	34.00	36.10	38.50
36	35.00	37.10	39.50
37	36.00	38.10	40.50
38	37.00	39.10	41.50
39	38.00	40.10	42.50
40	39.00	41.10	43.50

UNITS mm	MAT'L	FINISH	Q'TY
X.± 0.3	X.± 5'	X.± 2'	X.± 1'
X.± 0.25	X.± 2'	X.± 1'	X.± 0.5'
.XX± 0.20	.XX± 1'	.XX± 0.5'	.XX± 0.10
.XXX± 0.10	.XXX± 0.5'		

**QWYCONN** 深圳市启威源电子有限公司  
 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.

PART NO.(INTENDED USE) **1.0-A-nPW**  
 APPD:  
 CHKD:  
 DR: HU 2016.09.25

TITLE: **1.0单面接弯插**  
 DWG NO.: **1.0-A-nPW**

SCALE: 1/1  
 SHEET: 1/1  
 REV: A

安装开孔  
未注公差: ±0.05mm

扁平电缆