


PIN NO.	NAME	TYPE	DESCRIPTION
1	DATE	I/O/PP	DATE LINE(BIT2)
2	CD/DAT3	I/O/PP	CARD DETECT DATE LIN(BIT3)
3	CMD	PP	COMMAND RESPONSE
4	VDD	S	SUPPLY VOLTAGE
5	CLK	I	CLOCK
6	VSS	S	SUPPLY VOLTAGE GROUND
7	DAT0	I/O/PP	DATE LINE(BIT0)
8	DAT1	I/O/PP	DATE LINE(BIT1)



X± 0.3	X± 5'
X± 0.25	X± 2'
XXX± 0.20	XX± 1'
XXX± 0.10	XXX± 0.5'

UNITS mm	MATL	FINISH	QTY
PCS			
PART NO.(INTENDED USE) TF-PUSH CARD		TITLE: TF外焊自弹卡座	
APPD:		DWG NO.: TFW6-EBS1-1102	
CHKD:		SCALE 1/1	
DR: HU 2016.09.28		SHEET 1/1	
		REV. A	

QWYCONN 深圳市启威源电子有限公司
SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.

- NOTES:
- 1.MATERIAL:
HOUSING: HIGH TEMPERATURE THERMOPLASTIC
UL94V_0.COLOR:BLACK.
CONTACT: COPPER ALLOYS.
COVER: COPPER ALLOYS OR STEEL.
 - 2.PLATING:
UNDERPLATE: NICKEL.
CONTACT AREA: GOLD OVER NICKEL.
SOLDER AREA: TIN OVER NICKEL.
 - 3.MULTIMEDIA CARD COMPATIBLE