


PCB LAYOUT



备注：  
 塑胶：PBT+25%GF (UL 94V-0)  
 端子：磷铜C5191 R-H 镍底  
 50u"Min. 表面镀亮锡200u"Min.  
 性能：  
 额定电流：1A, AC/DC  
 额定电压：200V  
 接触阻抗：30mΩ Max.  
 绝缘阻抗：1000MΩ MIN.  
 耐电压值：500V RMS  
 工作温度：-55℃ t<sub>o</sub> +85℃.  
 标记⊗为FAI尺寸，标记⊕为重点  
 管控及首件检测尺寸

Δ	PIN	ΔP/N	A	B	备注
2	11134-002003	10.74	2.54		
3	11134-003005	13.28	5.08		P
4	11134-004001	15.82	7.62		V
5	11134-005003	18.36	10.16		C
6	11134-006004	20.90	12.70		
7	11134-007004	23.44	15.24		收
8	11134-008007	25.98	17.78		缩
9	11134-009001	28.52	20.32		袋
10	11134-010001	31.06	22.86		
11	11134-011001	33.60	25.40		
12	11134-012005	36.14	27.94		
13	11134-013005	38.68	30.48		
14	11134-014001	41.22	33.02		
15	11134-015003	43.76	35.56		
16	11134-016003	46.30	38.10		
17	11134-017004	48.84	40.64		
18	11134-018005	51.38	43.18		
19	11134-019001	53.92	45.72		
20	11134-020003	56.46	48.26		
21	11134-021001	59.00	50.80		
22	11134-022001	61.54	53.34		
23	11134-023001	64.08	55.88		
24	11134-024001	66.62	58.42		
25	11134-025001	69.16	60.96		
26	11134-026001	71.70	63.50		
27	11134-027001	74.24	66.04		

UNITS mm	FINISH	QTY	PCCS
MATL			
X± 0.3	X± 5'		
X± 0.25	X± 2'		
XX± 0.20	XX± 1'		
XXX± 0.10	XXX± 0.5'		
PART NO.(INTENDED USE) 2.54-A-nP		TITLE: 2.54MM 180° 薄膜插座	
APPD: 2.54-A-nP		DWG NO.: 2.54-A-nP	
CHKD: HU 2016.09.28		SCALE 1/1	SHEET 1/1
DR: HU 2016.09.28		REV. A	

**QWYCONN** 深圳市启威源电子有限公司  
 SHENZHEN QIWEIYUAN ELECTRONIC CO., LTD.